

3200 SERIES PUMP PRODUCT TECHNICAL DATA SHEET

OEM: 3214-2E1-73B

AFTERMARKET: 3214-2E1-73B-B (Includes Fittings, Retail Packaging)

APPLICATION: Agricultural, Chemical and Sprayer application intermittent duty only. This pump is not listed for potable water use.

PUMP DESIGN:

Type: 3 Chamber Positive Displacement Diaphragm
 Maximum Flow: 3.5 GPM [13.25 LPM]
 Fluid Ports: 3/4" Quick Attach Female
 Liquid: 140 F [60 C] MAX
 Dry Prime: 10 feet [4.2M]
 Run Dry: Yes
 Shut Off Pressure: 60 PSI [4.1 Bar]
 Control: Bypass



Electrical:

Motor: 24 VDC Permanent Magnet, Intermittent Duty
 Voltage Range: 23 VDC – 27.5 VDC
 Max Amps: 5 Amps
 Protection: Thermal Overload
 Leads: 14 AWG, 6" [15cm] 2 pin Connector
 Fuse: 7.5 Amp recommended
 Control: Bypass
 Max Temp: 180 F [82 C]

Materials of Construction

Housing: Polypropylene
 Valves: Viton
 Diaphragm: Santoprene
 Base: Metal Base
 Hardware: Zinc Plated Steel

AGENCY APPROVALS:

CE, CSA, RoHs, NSF

SHIPPING INFORMATION:

Part Net Weight: 6 lbs [3.62 kg]
 Carton Quantity: 6 Units
 Carton Size: 6" x 22" x 17.75"
 Carton Weight: 38 lbs [17.23 kg]



PSI	GPM	BAR	LPM	Amperage
0	3.50	0.00	13.25	2.85
10	3.25	0.69	12.30	3.25
20	3.00	1.38	11.36	3.95
30	2.75	2.07	10.41	4.20
40	2.50	2.76	9.46	4.55
50	2.00	3.45	7.57	5.00
60	1.75	4.14	6.62	5.10

10425 Wildlife Loop SE, Osakis, MN 56360

Office: 763-253-4740 Fax: 763-253-4741

www.remcoindustries.com

HEAT RISE 3214-2E1-73B

