

REMCO INDUSTRIES

5500 SERIES PRODUCT TECHNICAL DATA SHEET

OEM: 5516-2K1-63B
 AFTERMARKET: 5516-2K1-63B-B (Includes Fittings)

APPLICATION: Agricultural Chemical and Sprayer application intermittent duty only. This pump is not listed for potable water use.



PUMP DESIGN:

Type: 5 chamber, positive displacement diaphragm
 Maximum Flow: 4.0 GPM [15.14 LPM]
 Fluid Ports: ¾" Quick Attach Female
 Liquid Temp: 140 F [50 C]
 Prime: 14 feet [4.2M]
 Run Dry: Yes
 Pressure Setting: 150 PSI [10.3 Bar]
 Label: Remco Label, Part #, Specs, Serial #, MFG date

ELECTRICAL:

Motor: 12 VDC Permanent Magnet, Intermittent duty, Sealed motor
 Voltage Range: 11.5 VDC – 14.5 VDC
 Max Amps: 20 Amps Max at 150 PSI
 Leads: 14 AWG, 5.5" [13.9cm], 2 pin connector
 Fuse: 25 Amp Recommended
 Control: Bypass
 Max Temp: 180 F [82 C]
 IP Rating: IP65



MATERIALS OF CONSTRUCTION:

Housings: Polypropylene
 Valves: Viton
 Diaphragm: Santoprene
 Base: Welded
 Hardware: Zinc plated screws

AGENCY APPROVALS:

CE, RoHs

SHIPPING INFORMATION:

Net Weight: 8 lbs [3.62 kg]
 Carton Qty: 6 units
 Carton Weight: 42 lbs [19.05 kg]
 Carton Size: 6" x 22" x 17.75"

PSI	GPM	BAR	LPM	Amperage
0	4.10	0.00	15.52	7.50
20	3.75	1.38	14.20	9.00
40	3.05	2.76	11.55	12.50
60	2.45	4.14	9.27	15.00
80	2.00	5.52	7.57	16.50
100	1.40	6.90	5.30	17.00
120	1.30	8.28	4.92	18.50
140	1.15	9.66	4.35	19.00
150	0.95	10.34	3.60	19.50

4605 County Road 82 SE, Alexandria MN, 56308
 Office: 763-253-4740 Fax: 763-253-4741
www.remcoindustries.com

HEAT RISE 5516-2K1-63B

