

5500 SERIES PRODUCT TECHNICAL DATA SHEET

OEM: 5517-2E1-731B
 AFTERMARKET: 5517-2E1-731B-B (Includes Fittings, Single Box)

APPLICATION: Agricultural Chemical and Sprayer application intermittent duty only. This pump is not listed for potable water use.



PUMP DESIGN:

Type: 5 chamber, positive displacement diaphragm
 Maximum Flow: 5.3 GPM [20.05 LPM]
 Fluid Ports: 3/4" Quick Attach Female
 Liquid Temp: 140 F [50 C]
 Prime: 14 feet [4.2M]
 Run Dry: Yes
 Pressure Setting: 60 PSI [4.1Bar]
 Label: Remco Label, Part #, Specs, Serial #, MFG date

ELECTRICAL:

Motor: 24 VDC Permanent Magnet, Intermittent duty, Sealed motor
 Voltage Range: 23 VDC – 27.5 VDC
 Max Amps: 9 Amps Max at 60 PSI
 Leads: 14 AWG, 12" [30 cm], 2 pin connector
 Fuse: 10 Amp Recommended
 Control: Bypass
 Max Temp: 180 F [82 C]
 IP Rating: IP65

MATERIALS OF CONSTRUCTION:

Housings: Polypropylene
 Valves: Viton
 Diaphragm: Santoprene
 Base: Welded
 Hardware: Zinc plated screws

AGENCY APPROVALS:

CE, RoHs

SHIPPING INFORMATION:

Net Weight: 8 lbs
 Carton Qty: 6
 Carton Weight: 42 lbs
 Carton Size: 6" x 22" x 17.75"



PSI	GPM	BAR	LPM	Amperage
0	5.30	0.00	20.06	4.25
10	5.11	0.69	19.34	4.75
20	4.75	1.38	17.98	5.50
30	4.30	2.07	16.28	6.75
40	3.85	2.76	14.57	7.25
50	3.40	3.45	12.87	7.75
60	3.00	4.14	11.36	8.50

HEAT RISE 5517-2E1-731B

