

# REMCO INDUSTRIES

## 5500 SERIES PRODUCT TECHNICAL DATA SHEET

OEM: 5536-111-63B  
 AFTERMARKET: 5536-111-63B-B (Includes Fittings)

**APPLICATION:** Agricultural Chemical and Sprayer application intermittent duty only. This pump is not listed for potable water use.



### **PUMP DESIGN:**

Type: 5 chamber, positive displacement diaphragm  
 Maximum Flow: 4.0 GPM [15.14 LPM]  
 Fluid Ports: 1/2" FNPT  
 Liquid Temp: 140 F [50 C]  
 Prime: 14 feet [4.2M]  
 Run Dry: Yes  
 Pressure Setting: 100 PSI [6.9 Bar]  
 Label: Remco Label, Part #, Specs, Serial #, MFG date

### **ELECTRICAL:**

Motor: 12 VDC Permanent Magnet, Intermittent duty, Sealed motor  
 Voltage Range: 11.5 VDC – 14.5 VDC  
 Max Amps: 17 Amps Max at 100 PSI  
 Leads: 14 AWG, 5.5" [13.9cm], 2 pin connector  
 Fuse: 20 Amp Recommended  
 Control: Pressure switch  
 Max Temp: 180 F [82 C]  
 IP Rating: IP65



### **MATERIALS OF CONSTRUCTION:**

Housings: Polypropylene  
 Valves: Viton  
 Diaphragm: Santoprene  
 Base: Welded  
 Hardware: Zinc plated screws

### **AGENCY APPROVALS:**

CE, RoHs

### **SHIPPING INFORMATION:**

Net Weight: 8 lbs [3.62 kg]  
 Carton Qty: 6 units  
 Carton Weight: 42 lbs [19.05 kg]  
 Carton Size: 6" x 22" x 17.75"

PSI	GPM	BAR	LPM	Amperage
0	4.10	0.00	15.52	7.50
10	4.00	0.69	15.14	8.50
20	3.75	1.38	14.20	9.00
30	3.40	2.07	12.87	11.00
40	3.05	2.76	11.55	12.50
50	2.75	3.45	10.41	14.00
60	2.45	4.14	9.27	15.00
70	2.25	4.83	8.52	15.50
80	2.00	5.52	7.57	16.50
90	1.85	6.21	7.00	17.00
100	1.55	6.90	5.87	17.00

4605 County Road 82 SE, Alexandria MN, 56308  
 Office: 763-253-4740 Fax: 763-253-4741  
[www.remcoindustries.com](http://www.remcoindustries.com)

## HEAT RISE 5536-111-63B

