

5500 SERIES PRODUCT TECHNICAL DATA SHEET

OEM: 5536-2E1-58C
AFTERMARKET: 5536-2E1-58C-B

APPLICATION: Agricultural Chemical and Sprayer application intermittent duty only. This pump is not listed for potable water use.



PUMP DESIGN:

Type: 5 chamber, positive displacement diaphragm
Maximum Flow: 4.0 GPM [15.14 LPM]
Fluid Ports: 1/2" FNPT
Liquid Temp: 140 F [50 C]
Prime: 14 feet [4.2M]
Run Dry: Yes
Pressure Setting: 60 PSI [4.1Bar]
Label: Remco Label, Part #, Specs, Serial #, MFG date

ELECTRICAL:

Motor: 110/120 VAC Permanent Magnet, Intermittent duty
Voltage Range: 11.5 VDC – 14.5 VDC
Max Amps: 3 Amps
Leads: 4' [1.20m] cord with 3 prong plug
Fuse: 5 Amp Recommended
Control: Bypass
Max Temp: 180 F [82 C]
IP Rating: IP54

MATERIALS OF CONSTRUCTION:

Housings: Polypropylene
Valves: Viton
Diaphragm: Santoprene
Base: Welded
Hardware: Zinc plated screws

AGENCY APPROVALS:

CE, RoHs

SHIPPING INFORMATION:

Net Weight: 8 lbs [3.63 kg]
Carton Qty: 6 units
Carton Weight: 42 lbs [19.05 kg]
Carton Size: 6" x 22" x 17.75"



PSI	GPM	BAR	LPM	Amperage
0	4.10	0.00	15.52	0.70
10	4.00	0.69	15.14	0.80
20	3.75	1.38	14.20	0.90
30	3.40	2.07	12.87	1.00
40	3.05	2.76	11.55	1.10
50	2.75	3.45	10.41	1.20
60	2.45	4.14	9.27	1.30

HEAT RISE 5536-2E1-58C

