

**POWER RV FRESH WATER PUMP PRODUCT TECHNICAL DATA SHEET**

**OEM:** 55REBEL-65C

**AFTERMARKET:** 55REBEL-56C-B (Includes Fittings)

**APPLICATION:** Fresh Water Pumping applications (water only)

**PUMP DESIGN:**

Type: 5 Chamber Positive Displacement Diaphragm Pump  
 Maximum Flow: 5.3 GPM [20.06 LPM]  
 Fluid Ports: 3/4" Quick Attach Female  
 Liquid: 140 F [60 C] MAX  
 Dry Prime: 14 feet [4.2M]  
 Run Dry: Yes  
 Shut Off Pressure: 55 PSI [3.8 Bar]  
 Control: Dual control Pressure Switch/Bypass



**Electrical:**

Motor: 110 VAC Permanent Magnet, Intermittent Duty  
 Voltage Range: 110 VAC – 120 VAC  
 Max Amps: 3 Amps  
 Protection: Thermal Overload  
 Leads: 6ft [2.1M] Cord with 3 prong plug  
 Fuse: 5 Amp recommended  
 Control: Pressure Switch  
 Max Temp: 180 F [82 C]

**Materials of Construction**

Housing: Polypropylene  
 Valves: EPDM  
 Diaphragm: Santoprene  
 Base: Metal base with Grommets  
 Hardware: Stainless Steel

**AGENCY APPROVALS:**

CE, CSA, RoHs, UL

**SHIPPING INFORMATION:**

Part Net Weight: 8.0 lbs [3.62 kg]  
 Carton Quantity: 6 Units  
 Carton Size: 6" x 22" x 17.75"  
 Carton Weight: 42 lbs [ 17.23 kg]

PSI	GPM	BAR	LPM	Amperage
0	5.30	0.00	20.06	1.00
10	5.10	0.69	19.31	1.00
20	4.75	1.38	17.98	1.25
30	4.30	2.07	16.28	1.25
40	3.85	2.76	14.57	1.50
50	3.40	3.45	12.87	1.50
60	2.75	4.14	10.41	1.75

## HEAT RISE 55REBEL-65C

